

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended) An assembly comprising a steering wheel and a vibration damping device, said vibration damping device comprising:

a damping ~~means~~ unit arranged in said steering wheel,

an attenuation mass mounted for vibration movement in said steering wheel and connected with said damping ~~means~~ unit, and

a sensor for sensing a vibration parameter of the steering wheel and providing a variable output signal depending upon the value of the vibration parameter,

an electrical control unit coupled with said damping ~~means~~ unit to actuate said damping ~~means~~ unit,

said control unit ~~being able to~~, after actuation of said damping ~~means~~ unit, ~~further control said damping means to alter~~ in response to said variable output signal of said sensor changing mechanical vibration characteristics of said device such that different vibration frequencies can be damped based on the present value of the vibration parameter of the steering wheel.

Claim 2 (Currently Amended) The assembly according to Claim 1, wherein said damping ~~means~~ unit is designed such that said

mechanical vibration characteristics of said device can be altered by supplying electrical energy to said damping ~~means~~ unit.

Claim 3 (Canceled)

Claim 4 (Currently Amended) The assembly according to Claim 2, wherein said damping ~~means~~ unit comprises a material ~~which~~ alters mechanical characteristics , wherein the mechanical vibration characteristics of the material alter with said supply of electrical energy to said damping unit.

Claim 5 (Canceled)

Claim 6 (Previously Presented) The assembly according to Claim 4, wherein said material is an electrorheological fluid.

Claim 7 (Canceled)

Claim 8 (Canceled)

Claim 9 (Currently Amended) An assembly comprising a steering wheel and a vibration damping device, said vibration damping device comprising:

a damping ~~means~~ unit including a hollow damping body arranged in said steering wheel,

a mass core acting as an attenuation mass arranged inside said hollow damping body, and

an electrical control unit coupled with said damping ~~means~~ unit, said electrical control unit being able to alter mechanical vibration characteristics of said damping ~~means~~ unit such that different vibration frequencies can be damped.

Claim 10 (Previously Presented) The assembly according to claim 9, wherein said hollow damping body is made of an elastic material.

Claim 11 (Previously Presented) The assembly according to claim 9, wherein said hollow damping body is ring-shaped.

Claim 12 (Currently Amended) The assembly according to Claim 1, wherein said damping ~~means~~ unit includes a hollow body made of an elastic material.

Claim 13 (Previously Presented) The assembly according to Claim 12, wherein said hollow body is ring-shaped.

Claim 14 (Canceled)

Claim 15 (Previously Presented) The assembly according to Claim 12, wherein said hollow body contains one of an electrorheological and magnetorheological fluid.

Claim 16 (Currently Amended) An assembly comprising a steering wheel and a vibration damping device, said vibration damping device comprising:

a damping ~~means~~ unit including a hollow damping body arranged in said steering wheel,

a mass core acting as an attenuation mass arranged inside said hollow damping body, and

an electrical control unit coupled with said damping ~~means~~ unit, said electrical control unit being able to alter mechanical vibration characteristics of said device such that different vibration frequencies can be damped,

said hollow damping body containing one of an electrorheological fluid and a magnetorheological fluid.

Claim 17 (Canceled)

Claim 18 (New) The assembly according to claim 16 including a sensor for sensing the vibration frequency of the steering wheel and providing a variable output signal depending upon the vibration frequency, and wherein said control unit, after actuation of said damping unit, in response to said variable output signal of said sensor changing mechanical vibration characteristics of said device such that different vibration frequencies can be damped based on the present vibration frequency of the steering wheel.

Claim 19 (New) The assembly according to claim 9 including a sensor for sensing the vibration frequency of the steering wheel and providing a variable output signal depending upon the vibration frequency, and wherein said control unit, after actuation of said damping unit, in response to said variable

output signal of said sensor changing mechanical vibration characteristics of said device such that different vibration frequencies can be damped based on the present vibration frequency of the steering wheel.

Claim 20 (New) The assembly according to claim 19, wherein said hollow damping body is made of an elastic material.

Claim 21 (New) The assembly according to claim 19, wherein said hollow damping body is ring-shaped.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.